



14700 Downey Avenue  
P.O. Box 1418  
Paramount, CA 90723-1418  
(562) 531-2060

**PRODUCT SPECIFICATIONS**

**PRODUCT:** High Performance Seal

**GRADE:**

**PRODUCT CODE:** 13828

**DESCRIPTION:** A hot-applied, quick-setting asphalt sealer for filling cracks and pavement surface imperfections, resulting in a wearing course that is immediately available for traffic. Also excellent as a hot-applied no-track tack coat.

**MEETS SPECIFICATIONS:** Paramount Petroleum Corp.

TESTS	ASTM METHOD	AASHTO METHOD	SPECS.	TYPICAL ANALYSIS*
Original Asphalt:				
Rotational Viscosity, 275°F, cP	D4402	T316	3500 max	2000
Rotational Viscosity, 350°F, cP	D4402	T316	300 max	185
Penetration, 77°F, 100g, 5s	D5	T49	9 min	10
Flash Point, C.O.C., °F	D92	T48	450 min	595
Softening Point °C	D36	T53	170 min	175
Solubility in TCE, wt %	D2042	T44	97.5 min	98.5
Specific Gravity, 77/77°F	D70	T228		1.018
Specific Gravity, 60/60°F	D70	T228		1.024
API Gravity, 60°F	D70	T228		6.7
Density, 60F, Lbs/Gallon	D70	T228		8.53
Tire Rubber Content, %			1 - 4	3

\*Values shown as typicals may, at times, be superseded by results, which are current at a particular time.

**AVAILABILITY:** Special Order

**DOT SHIPPING NAME:** UN3257, Elevated temperature liquid, n.o.s., 9, III

**RELEASED:** 09/01/04